



# CERTIFICATION RECORD

The company named below has been authorized by CSA International to represent the products listed in this record as "CSA Certified" and to affix the CSA Mark to these products according to the terms and conditions of the CSA Service Agreement and applicable CSA program requirements (including additional Markings).

File No: 211224

Class No: 4211 81 MOTORS AND GENERATORS Certified to US Standards

## SUBMITTOR

4661518 Valtaro Motori S.r.l.  
Via Primo Brindani 33  
Borgo Val di Taro, Parma 43043  
Italy

## FACTORIES

4661518 Valtaro Motori S.r.l.  
Via Primo Brindani 33  
Borgo Val di Taro, Parma 43043  
Italy

December 30, 2010 (Replaces: May 25, 2005)

## TO THE REQUIREMENTS OF UL STANDARD 1004

- Squirrel-cage induction motors, Series MM, Single phase, 4 poles, frame size, from 56 to 100, TEFC, insulation Class F, horizontal or vertical, foot of flange mounting, 230V or less, 60 Hz, 2.2kW max.
- Squirrel-cage induction motors, Series M, Three phase, 2 through 6 poles, frame size, from 56 to 132, insulation Class F, horizontal or vertical, flange mounting, 600V or less, 50 or 60 Hz, 11.0 kW max.

*Squirrel cage induction motors for operation submerged in hydraulic oil, component type, oil temperature*

*60 °C max, duty cycle 30%.*

### Part A:

400 V or less, 3-ph, 60 Hz. Ins. Class F, 2 or 4 poles, types BO4xx60 and BO2xx60, from 0.75 to 4 kW, frame size 135 mm.

### Part B:

230 V or less, 1-ph, 60 Hz, Ins. Class F, 2 or 4 poles, types BO4xx60 and BO2xx60, from 0.75 to 2.2 kW,

frame size 135 mm.

/rb